

SAFETY DATA SHEET

SLUICE WASH

Page 1
Issued: 08/08/2005
Revision No: 1

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: SLUICE WASH

Product code: 337

Use / description of product: 337 : A specialised cleaner for automatic cleaning machines in the health sector.

Company name: Clover Chemicals Ltd
Clover House
Macclesfield Road
Whaley Bridge, High Peak
Derbyshire
SK23 7DQ
UK
Tel: +44 (0) 1663 733114
Fax: +44 (0) 1663 733115

2. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: /-TRISODIUM NITRILOTRIACETATE 10-30%
EINECS: 225-768-6 CAS: 5064-31-3
[Xn] R22; [Xi] R36

- SODIUM HYDROXIDE 10-30%
EINECS: 215-185-5 CAS: 1310-73-2
[C] R35

3. HAZARDS IDENTIFICATION

Main hazards: Causes severe burns.

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: Blistering may occur. Progressive ulceration will occur if treatment is not immediate.

Eye contact: Corneal burns may occur. May cause permanent damage.

Ingestion: Corrosive burns may appear around the lips. Blood may be vomited. There may be bleeding from the mouth or nose.

Inhalation: There may be shortness of breath with a burning sensation in the throat. Exposure may cause coughing or wheezing.

4. FIRST AID MEASURES (ACTION)

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Transfer to hospital if there are burns or symptoms of poisoning.

Eye contact: Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.

[cont...]

SAFETY DATA SHEET

SLUICE WASH

Ingestion: Wash out mouth with water. Do not induce vomiting. Give 1 cup of water to drink every 10 minutes. If unconscious, check for breathing and apply artificial respiration if necessary. If unconscious and breathing is OK, place in the recovery position. Transfer to hospital as soon as possible.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. If unconscious and breathing is OK, place in the recovery position. If conscious, ensure the casualty sits or lies down. If breathing becomes bubbly, have the casualty sit and provide oxygen if available. Transfer to hospital as soon as possible.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

Exposure hazards: Corrosive. In combustion emits toxic fumes.

Protection of fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Notify the police and fire brigade immediately. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Do not create dust.

Environmental precautions: Do not discharge into drains or rivers.

Clean-up procedures: Clean-up should be dealt with only by qualified personnel familiar with the specific substance. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

7. HANDLING AND STORAGE

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of dust in the air.

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Stainless steel. Teflon. Polyethylene.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Hazardous ingredients: SODIUM HYDROXIDE
TWA 2 mg/m³ STEL 2 mg/m³

Hand protection: Protective gloves.

Eye protection: Tightly fitting safety goggles. Ensure eye bath is to hand.

Skin protection: Protective clothing.

SAFETY DATA SHEET

SLUICE WASH

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Liquid
Colour: Yellow-orange
Odour: Barely perceptible odour
Evaporation rate: Moderate
Solubility in water: Soluble
Viscosity: Non-viscous
Relative density: 1.05 - 1.15
pH: 1% = 12 - 12.5

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions.
Conditions to avoid: Heat.
Materials to avoid: Strong oxidising agents. Strong acids.
Haz. decomp. products: In combustion emits toxic fumes.

11. TOXICOLOGICAL INFORMATION

Hazardous ingredients: SODIUM HYDROXIDE
IPR MUS LD50 40 mg/kg
ORL RBT LDLO 500 mg/kg

Routes of exposure: Refer to section 4 of SDS for routes of exposure and corresponding symptoms.

12. ECOLOGICAL INFORMATION

Persistence and degradability: Biodegradable.
Bioaccumulative potential: No bioaccumulation potential.
Other adverse effects: Negligible ecotoxicity.

13. DISPOSAL CONSIDERATIONS

Disposal of packaging: Dispose of as normal industrial waste.
NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

14. TRANSPORT INFORMATION**ADR / RID**

UN no: 1719	ADR Class: 8
Packing group: II	Classification code: C5
Shipping name: CAUSTIC ALKALI LIQUID, N.O.S. (SODIUM HYDROXIDE (12%))	
Labelling: 8	Hazard ID no: 80

SAFETY DATA SHEET

SLUICE WASH

**IMDG / IMO**

UN no: 1719	Class: 8
Packing group: II	EmS: F-A,S-B
Marine pollutant: .	Labelling: 8

IATA / ICAO

UN no: 1719	Class: 8
Packing group: II	Packing instructions: 809(P&CA); 813(CAO)
Labelling: 8	

15. REGULATORY INFORMATION**Hazard symbols:** Corrosive.**Risk phrases:** R35: Causes severe burns.

Safety phrases: S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S36/37/39: Wear suitable protective clothing, gloves and eye / face protection.

S45: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

Seveso II guideline: No**Water hazard class:** 1 Classification by VwVwS

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

16. OTHER INFORMATION

Risk phrases used in s.2: R22: Harmful if swallowed.

R36: Irritating to eyes.

R35: Causes severe burns.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.